



GROUT SEALER

TECHNICAL DATA SHEET



PRODUCT DESCRIPTION

Grout Sealer is a water-based formulation utilizing high-quality acrylic emulsions and select additives, designed to seal and prevent surface wear of grouts, water penetration and to protect grouts from household acid-based contaminants, grease and oil.

Available in 1-liter bottles.

ADVANTAGES

- Will not change the color of the grout
- Water-based
- Easy to apply
- Protects against most common stains

ENVIRONMENTAL INFORMATION

CementPro is committed to environmental responsibility in products produced and manufacturing practices.

WHERE TO USE

Cementitious grouts.

LIMITATIONS

- Do not allow the sealer to dry on tile surface.
- Do not allow the sealer to come in contact with any non-recommended surface.
- Grout Sealer will not prevent surface wear or etching from acids or caustic chemicals.

SURFACE PREPARATION

The surface must be dry, clean and free of oil, grease, paint, dust, dirt and foreign materials. Surface temperature should be between 50 - 90°F.

MIXING

Grout Sealer is ready to use.

GROUT SEALER

APPLICATION

Apply the sealer 48 hours after the grout installation.

1. Shake well.
2. Apply Grout Sealer directly onto grout lines and joints to thoroughly wet the surface using a soft brush or sponge. Avoid applying sealer on unintended surfaces.
3. Allow sealer to completely penetrate the grout, approximately 5– 10 minutes.
4. Remove any excess or non-absorbed sealer from the tile and grout with a clean, soft towel. If a residue is present, remove it with a clean, soft towel dampened with warm water.
5. Allow sealer to dry for at least 30 minutes, then apply a second coat following steps 1–4.

**Do not pour unused product back into the original container.*

Test a small section after 24 hours by applying a few drops of water on the grout surface. If it soaks in, an additional application of sealer will be necessary.

CURING

The newly sealed surface should stay dry and traffic free for 24 hours before use.

STORAGE

Store this product in a tightly closed container in a cool, dry and well-ventilated area. Do not allow the sealer to freeze.

CLEANING OF TOOLS

Immediately clean all tools with water.

DISPOSAL

Always dispose of products and packaging properly and in accordance with local, state and federal guidelines.

COVERAGE

Will vary depending on the porosity and texture of the grout surface, temperature, humidity and application method. 1qt. covers approximately 15 - 32 ft² (1.39 - 2.97 m²)

MAINTENANCE

Routine cleaning using a neutral pH cleaner is recommended. Do not use cleaners containing ammonia, acids or bleach, as highly alkaline, acidic, ammoniated, or abrasive cleaners may degrade the sealer, adversely affecting performance. Periodic testing of sealed surfaces is advised by applying a few drops of water on the surface. If it soaks in, an additional application of sealer will be necessary.

EXPECTED DURATION OF PROTECTION

Protection will vary depending on the hardness and texture of the surface, type of area, surface wear, frequency and type of maintenance products used, weather conditions, harsh cleaning methods and high-alkaline, acidic, or solvent-based cleaners.



GROUT SEALER

PRECAUTIONARY STATEMENTS

Do not ingest. Avoid eye and skin contact, and wear approved safety equipment like goggles and gloves. Use in a well-ventilated area only. If eye contact occurs, flush immediately with water for 15 minutes and consult a physician. KEEP OUT OF REACH OF CHILDREN. Refer to MSDS for additional information.

WARRANTY

1-Year Product Limited Warranty. Obtain the applicable LIMITED PRODUCT WARRANTY at <https://cementpro.com/warranty/>. User determines the product's suitability for the intended use and assumes all risks. The user's and/or buyer's sole remedy shall be limited to this product's purchase price or replacement, excluding labor costs.

For Warranty Questions:

Write to: 3929 E Guasti Rd, Unit C Ontario, CA 91761

Call: (951) 300-0300 Ext. 600

Email: Warranty@cementpro.com

LEGAL DISCLAIMER

FOR PROFESSIONAL USE ONLY. Before using any CementPro product, the user must always read and follow the warnings and instructions on the product's most current product label, Technical Data Sheet and Material Safety Data Sheet, available at www.cementpro.com or by calling CementPro's Technical Service Department at 1-951-300-0300.

