



NON SANDED POLY-PRO

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

A premium blended polymer modified tile grout, blended with Portland cement and selected additives to produce excellent strength and workability for tile installations. Exceeds ANSI 118.6 when is mixed with clean potable water.

SURFACE PREPARATION

Tile surfaces should be clean and grouting can begin 24 - 72 hours after tile installation. Surfaces should be frost free for 72 hrs before grouting can begin. Consult TCA method EJ 171 for expansion joint placement.

PLACEMENT

Refer to current ANSI 108.1 specifications.





APPLICATION

Use clean potable water and clean mixing container. A full Box of POLY-PRO non-sanded grout needs approximately 1/2 gallon (1.8 liters) of water. Gradually add the contents of the bag to the water and mix thoroughly by hand or by using a slow speed drill and mixing device. Mix the material until lump free and into a thick and creamy consistency. Allow the grout to stand 10 to 15 minutes and mix again. Occasional mixing of the grout during use is recommended however, **DO NOT re-temper**. The addition of water (re-tempering) can reduce the materials performance, change the grout color and effect strength.

USES

POLY-PRO grout can be used on both walls, floors, interior and exterior applications on joints between 1/16 to 1/8 inch. This grout is suitable for residential and commercial installations.

CURING

The length of full curing depends on climate conditions, usually 24 to 72 hours. Allow for proper curing prior to sealing of grout.

COVERAGE PER BAG

Coverage will vary depending on tile size and joint width.
1 Box of 10 lb of POLY-PRO mixed with water covers 50 - 170 sq ft.

WARNINGS

This product contains Portland cement which contains greater than 0.1% crystalline silica. Prolonged or occupational exposure to airborne crystalline silica may cause lung disease or cancer. For detailed information on how to use and handle this product safely, see the Material Safety Data Sheet.

CEMENT PRO, as a manufacturer of processed material in the State of California, we are required by Proposition 65 to warn that one or more of the components contained in this product could contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California requires the above warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacture, distribution and intended use.

CAUTION

This material contains Portland cement, silica sand and polymers. Contact with dry or freshly mixed mortar, grout or concrete may cause skin irritation. If direct contact occurs wash exposed skin areas promptly with soap and water. If any cement material gets into the eyes, rinse immediately and repeatedly with water and seek prompt medical attention.

KEEP OUT OF REACH OF CHILDREN

WARRANTY

Recommendations for the use of this product are based on reliable tests. No guarantee of results is made where conditions are beyond our control. No representations either expressed or implied are made with respect to the product except as herein stated and under no circumstances, either expressed or implied, will CEMENT PRO be held liable for damages in excess of the purchase price of this product. Storage Life - One year if kept in a dry sealed bag.