



PRO CLEAN

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Formulated with high quality detergents, additives and soft acids. This product will clean and enhance the initial appearance of the grout. It will remove grease and dirt that have accumulated over time. This product is ready and safe to use.

APPLICATION

Apply a slightly damp layer of water over the grout, just enough to wet the surface for cleaning. Immediately apply the cleaner, spraying small areas at a time. Allow the cleaner to work into the surface for 2 or 3 minutes and then with a brush or sponge, scrub the surface areas to remove the hardened dirt and other contaminants. Immediately rinse clean with water. It is recommended to use the GROUT CLEANER 10 days after the grout installation to remove any remaining grout residue.

Do not use this product for your everyday cleaning. Excessive and over usage can result in surface damage. 1 to 2 times usage a year maximum is recommended. **DO NOT USE ON POLISHED MARBLE OR POLISHED STONES AND AVOID CONTACT WITH METALS.**





PRO CLEAN

TECHNICAL DATA SHEET

USES

PRO CLEAN also removes dried cement, grout haze and mortar residue from tile, concrete and masonry. Removes hard water deposits and efflorescence. Safe for using on most cement based colored grouts, tile, clay pavers, concrete and masonry. Before using any cleaner, do a sample test in a small inconspicuous area in order to verify satisfactory results.

COVERAGE

Coverage is approx. 75 sq. ft. (7 m²)

STORAGE

Store this product in a tightly closed container out of direct sunlight and in a dry place. Close this container after each use.

CAUTION

THIS PRODUCT CONTAINS DILUTED SULFAMIC ACID. Harmful or toxic if swallowed. Do not take internally Use only with adequate ventilation. If swallowed, immediately drink 1 or 2 glasses of water and call a physician. Avoid eye and skin contact, wear approved safety equipment, goggles and gloves, if eye contact occurs, flush immediately with water for 15 minutes and consult a physician. Refer to MSDS for additional information.

KEEP OUT OF REACH OF CHILDREN

WARRANTY

This material contains Portland cement, Silica sand and Vinyl Acetate Co-polymers. Contact with dry or freshly mixed mortar, grout, or concrete may cause skin irritation. Avoid direct contact where possible and wash exposed skin areas promptly with water. If any cement material gets into the eyes, rinse immediately and repeatedly with water and seek prompt medical attention.