



PRO MASTIC

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Pre-mixed water based acrylic adhesive, recommended for interior wall and floor installations. It is manufactured with styrene-acrylic emulsions, first quality additives, and graduated inert aggregates. **CEMENT PRO TILE ADHESIVE** is easy to spread and high bond strength. Exceeds ANSI A136.1 Type I.

SURFACE PREPARATION

Surfaces must be clean, dry, structurally sound, and free of dust, dirt, grease, waxes or other contaminant that would avoid the adequate adherence. Painted surfaces must be sanded, stripped and cleaned. It is recommended to repair all the cracks presented in the surface.

MIXING

PRO MASTIC is ready to use. Do not add more water. If it is necessary re-mix manually to homogeneous consistency.

STORAGE

3/16 x 5/32 in "V" notched 40-55 sq. ft.
1/4 x 1/4 in square notched 25-40 sq.ft.





APPLICATION

Spread the **PRO MASTIC** over the surface with an appropriate trowel using flat side. Immediately apply additional tile adhesive with notched side of trowel. Assure to leave a minimum of 80% of the material in contact with the tiles. Do not spread more adhesive than you can use in 20 minutes since it may superficially dry up. It is recommended to use 1/4 x 1/4 in square notched or 3/16 x 5/32 in "V" notched. Firmly place the tiles over the fresh adhesive with a slight movement to ensure correct joint. If there is superficial dry up, remove it and replace with fresh adhesive before placing more tiles. Immediately, make the necessary alignments and adjustments. Keep container closed when not in use.

USES

It is recommended to install ceramic over interior floor and wall. Suitable for wet areas such as tub surrounds and shower walls. It can be applied over concrete, masonry, plaster, backerboard, gypsum board and plywood. Do not use in exterior.

LIMITATIONS

Not to be used directly to lightweight concrete, parquet, metal, glass, plastic, gypsum mortar beds, particle board, OSB (chip board) or Masonite surfaces.

DRYING TIME

Under normal conditions allow a minimum of 24 – 36 hours before apply grout. DO NOT accelerate the curing of this material with mechanical fans or heating devices. Always do a test with the bonding adhesive to verify the suitability of the bond to the sub straight.

WARNING

Prolonged contact with eyes or skin can cause irritation. Use with adequate ventilation. Refer to material safety data sheet for additional information.

KEEP OUT OF REACH OF CHILDREN

WARRANTY

Recommendations for the use of this product are based on reliable tests. No guarantee of results is made where conditions are beyond our control. No representations either expressed or implied are made with respect to the product except as herein stated and under no circumstances, either expressed or implied, will Cement Pro LLC be held liable for damages in excess of the purchase price of this product.