



REMOVER PRO

TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Remover-Pro is the eco-friendly, liquid cleaner formulated to easily break down dried cement, and help maintain the tools of the trade professional. This safe alternative to the harmful acidic cleaners is non-fuming, non-corrosive, and 100% biodegradable.

SURFACE PREPARATION

DO NOT wet surface to be cleaned. Diluting with water will neutralize the effects of this product. Simply spray directly onto the dried cement (concrete, masonry, mortar or stucco) you wish to remove. Once completely saturated, allow Remover-Pro approximately 10-15 minutes to attack and break down the desired area to be cleaned. As the surface dries, a white residue will begin to appear. Reapply to maintain saturation and ensure the most effective results. When the cement softens into a pasty-like texture, rinse with cold water using a garden hose with a pressure washer attachment. Remover-Pro begins working quickly, but the results are not immediate. For difficult or thick cement, you may have to repeat the required steps to achieve desired results. Cement based product will soften and release from surface in a total time of approximately 20-30 minutes.



Rinse with cold water using high pressure washer or a garden hose with a pressure nozzle. On extra thick build up, repeat cleaning directions until build up has softened. In complicated areas or high thickness, multiple applications may be required and could be helped mechanically.

REMOVER-PRO acts quickly, but is not an instantly reaction, follow the steps indicated in order to have success in the removal and cleaning.



REMOVER PRO

TECHNICAL DATA SHEET

MIXING

This product is ready to use. No mixing required. DO NOT add any water.

APPLICATION

Do not wet surface before application. Completely saturate area of hardened cement based product (concrete, masonry, mortar or stucco) to be removed with **REMOVER-PRO**. Surface will be turn white as the product begins to react, breakdown the material. Allow **REMOVER-PRO** to penetrate between 10 to 15 minutes. Then re-apply to the same area. Keep in every moment the surface wet with the remover. A white residue will appear once the cleaner evaporates. Re-apply the product to reactivate until the dry cement has softened into a pasty consistency, then rinse or wipe away. Concrete and other cement based products will begin to soften and release from surface in a total time of approximately 20 – 30 minutes. Rinse with cold water using high pressure washer or a garden hose with a pressure nozzle. On extra thick build up, repeat cleaning directions until build up has softened. In complicated areas or high thickness, multiple applications may be required and could be helped mechanically. **REMOVER-PRO** acts quickly, but is not an instantly reaction, follow the steps indicated in order to have success in the remotion and cleaning.

USES

REMOVER-PRO is formulated for dissolving cured cement (concrete, masonry, mortar, stucco or grout) of tools and other surfaces. It can be used to clean dried concrete residue on siding, vinyl, wooden decks, etc. without damaging the surface. See limitations before using.

COVERAGE

Variable depending on the surface to clean.

TECHNICAL INFORMATION

Color	Green
Base	Organic acids
pH	3
Specific gravity	1.05

LIMITATIONS

Do not use on concrete pavers. Do not apply when the temperature is below 50 degrees F or above 90 degrees F. Always provide adequate ventilation when using indoors.

WARNINGS

This product contains Portland cement which contains greater than 0.1% crystalline silica. Prolonged or occupational exposure to airborne crystalline silica may cause lung disease or cancer. For detailed information on how to use and handle this product safely, see the Material Safety Data Sheet.

CEMENT PRO, as a manufacturer of processed material in the State of California, we are required by Proposition 65 to warn that one or more of the components contained in this product could contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California requires the above warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacture, distribution and intended use.



REMOVER PRO

TECHNICAL DATA SHEET

CAUTION

This material contains Portland cement, silica sand and polymers. Contact with dry or freshly mixed mortar, grout or concrete may cause skin irritation. If direct contact occurs wash exposed skin areas promptly with soap and water. If any cement material gets into the eyes, rinse immediately and repeatedly with water and seek prompt medical attention.

KEEP OUT OF REACH OF CHILDREN

WARRANTY

Recommendations for the use of this product are based on reliable tests. No guarantee of results is made where conditions are beyond our control. No representations either expressed or implied are made with respect to the product except as herein stated and under no circumstances, either expressed or implied, will CEMENT PRO be held liable for damages in excess of the purchase price of this product. Storage Life - One year if kept in a dry sealed bag.