



ELASTIC PRO

MATERIAL SAFETY DATA SHEET

Creates a continuous waterproofing barrier with great adhesion and reduces crack transmission in tile and stone floors.

1 PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME:

ELASTIC PRO

CHEMICAL FAMILY:

Pre-mixed acrylic based waterproofing membrane

MANUFACTURER:

CEMPRO LLC
3929 E Guasti Rd Unit C.
Ontario, Ca 91761
phone: 951 300 0300
www.cementpro.com



2 COMPOSITION AND INFORMATION ON INGREDIENTS

INGREDIENT	CAS NUMBER	PERCENT (WT)
Calcium carbonate	1317-65-3	20 – 40%
Acrylic polymer	Not establish	20 – 40%
Attapulgitte clay	Not establish	< 5%
Ethylene glycol	107-21-1	< 5%

3 HAZARDS IDENTIFICATION

Inhalation exposure: The vapors and dust produced by this product can cause irritation to the respiratory tract.

Skin contact: Prolonged contact with skin can cause irritation.

Eyes contact: Can cause irritation.

Ingestion: May be harmful if ingested, causing gastrointestinal irritation, nausea and vomiting. Ingestion of large amounts of this product can cause liver, kidney and brain damage.

Chronic/Carcinogenicity effects: May contain traces of chemicals on CA Proposition 65 list.



4 FIRST AID MEASURES

Inhalation: Remove to fresh air. Get medical attention immediately.
Skin contact: Remove excess from the skin and promptly wash contaminated skin with water and soap or mild detergent. Get medical attention immediately if the irritation, redness, rash or blistering develops and persists.
Eye contact: Gently blot or wipe any residue remaining on the face. Flush eyes immediately with plenty of water for 15 minutes. Get medical attention immediately if the irritation persists.
Ingestion: Gently blot or wipe any residue remaining on the face. Flush eyes immediately with plenty of water for 15 minutes. Get medical attention immediately if the irritation persists

5 FIRE FIGHTING MEASURES

Flash point: Not applicable. NOT FLAMMABLE OR COMBUSTIBLE.
Flammable limits: Not applicable.
Autoignition Temperature: Not applicable.
Fire extinguishing materials: Water spray, foam, carbon dioxide, dry chemical.
Hazardous combustion product: Incomplete combustion of dried product can yield low molecular weight hydrocarbons, carbon monoxide, and carbon dioxide.
Special fire fighting procedures: Not applicable.
Unusual fire and explosion hazards: Not applicable.

6 DISPOSAL PROCEDURES

Avoid generating dust. Collect by sweeping and scooping. Transfer collected material to a container. Wear appropriate equipment to prevent skin and eyes contact and use a dust mask. For wet material, scoop up and transfer to a container, allow material to dry before disposal.
Note: Dispose of all wastes in accordance with federal, state and local regulations.

7 HANDLING AND STORAGE

Handling and storage precautions: Use only with adequate ventilation. Wear appropriate protective equipment. Keep the container closed when not in use.
Storage precautions: Store in cool, dry areas away from sunlight and heat. Avoid extremes temperatures in storage.

8 EXPOSURE CONTROL AND PERSONAL PROTECTION

Respiratory protection: A NIOSH approved dust mask if personal exposure cannot be controlled below applicable limits by ventilation.
Skin protection: Use impervious gloves if the hands will be exposed.
Eye protection: Safety glasses or goggles recommended.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Fluid paste aquamarine or blue color.
Odor: Odorless
Chemical type: Mixture
Physical state: Solid
Boiling point: Not applicable
Specific gravity: 2.1
Vapor density: Not applicable
Solubility: Dispersible
Evaporation rate: Not applicable
Voc: 0.0 lb/gal (0 g/l)



ELASTIC PRO

MATERIAL SAFETY DATA SHEET

- 10 STABILITY AND REACTIVITY** **Stability:** Stable
Hazardous polymerization: Will not occur.
Hazardous decomposition products: Will not spontaneously occur. By fire may yield low molecular weight hydrocarbons, carbon dioxide and monoxide.
Incompatibility: Avoid contact with strong oxidizers.
- 11 TOXICOLOGICAL INFORMATION** **Mineral dusts:** Some minerals mentioned in section 2 are considered mineral dusts by OSHA and a correctly fitted. An approved respirator is required when working with this product.
Ingredients / carcinogenicity: May contents traces of silica. May contain traces of chemicals on CA Proposition 65 list.
- 12 ECOLOGICAL INFORMATION** Not Available
- 13 DISPOSAL INFORMATION** This product must be disposed in compliance with local, state, and federal regulations.
- 14 TRANSPORT INFORMATION** DOT Shipping label. NOT REGULATED.
- 15 REGULATORY INFORMATION** **State regulation:**
Cement Pro LLC as a blender of processed material in the State of California, we are required by Proposition 65 to warn that one or more of the components contained in this product could contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. The State of California (Proposition 65) requires the above warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacture, distribution and intended use.
• Calcium carbonate 1317-65-3
Ethylene glycol, acrylic copolymer > California, Proposition 65.

OSHA: This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA).
EPA VOC Regulations: 0.0 lb/gal (0 g/l)
- 16 OTHER INFORMATION** **HMIS RATING**
HEALTH: 1
FIRE: 0
REACTIVITY: 0
PERSONAL PROTECTION: E