



# GROUT SEALER

MATERIAL SAFETY DATA SHEET

A water based formulation, designed to seal and prevent surface wear of grouts, water penetration, and to protect grouts from household acid based contaminants, grease and oil.

## 1 PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME:

GROUT SEALER

CHEMICAL FAMILY:

Acrylic based sealer

MANUFACTURER:

CEMPRO LLC  
3929 E Guasti Rd Unit C.  
Ontario, Ca 91761  
phone: 951 300 0300  
www.cementpro.com



## 2 COMPOSITION AND INFORMATION ON INGREDIENTS

INGREDIENT	CAS NUMBER	PERCENT (WT)
Styren acrylic copolymer	Not establish	20-40%

## 3 HAZARDS IDENTIFICATION

### CORROSIVE MATERIAL

**Inhalation exposure:** The vapors or dust when is dried can cause irritation to the respiratory tract.

**Skin contact:** Prolonged contact with skin can cause irritation.

**Eyes contact:** Can cause irritation.

**Ingestion:** May be harmful if ingested.

**Other information:** Not known to cause birth defects or cause reproductive harm.



## 4 FIRST AID MEASURES

**Inhalation:** Remove to fresh air. Get medical attention immediately.  
**Skin contact:** Promptly wash contaminated skin with water and soap or mild detergent. Get medical attention immediately if the irritation, redness, rash or blistering develops and persists.  
**Eye contact:** : Flush eyes immediately with plenty of water for 15 minutes. Get medical attention immediately if the irritation persists.  
**Ingestion:** DO NOT INDUCE VOMITING. Get medical attention immediately.

## 5 FIRE FIGHTING MEASURES

**Flash point:** > 200 °F.  
**NOT FLAMMABLE OR COMBUSTIBLE:** Water based product.  
**Flammable limits:** Not applicable.  
**Autoignition Temperature:** Not applicable.  
**Fire extinguishing materials:** Water spray, foam, carbon dioxide, dry chemical.  
**Hazardous combustion product:** Incomplete combustion of dried product can yield carbon monoxide, and carbon dioxide.  
**Special fire fighting procedures:** Not applicable.  
**Unusual fire and explosion hazards:** Not applicable.

## 6 DISPOSAL PROCEDURES

Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination. Contain and absorb spill with inert material, then place in a suitable container. Wear appropriate equipment to prevent skin and eyes contact.  
**Note:** Dispose of all wastes in accordance with federal, state and local regulations.

## 7 HANDLING AND STORAGE

**Handling and storage precautions:** Avoid contact with skin and eyes. Do not swallow. Do not breathe gas, vapor, fumes, spray. Handle and open container with care. Wear appropriate protective equipment.  
**Storage precautions:** Keep the container closed when not in use. Avoid extremes temperatures in storage.

## 8 EXPOSURE CONTROL AND PERSONAL PROTECTION

**Ventilation:** Use with adequate ventilation  
**Respiratory protection:** If you scrape, sand, or remove old paint before apply this product, you may release lead dust, that is toxic and must be avoided. In case of inadequate ventilation wear a NIOSH approved respirator.  
**Skin protection:** Use impervious gloves if the hands will be exposed.  
**Eye protection:** Safety glasses or goggles recommended.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** White milky liquid  
**Odor:** Mild acrylic odor  
**Chemical type:** Mixture  
**Physical state:** Liquid  
**Boiling point:** 190-210 °F  
**Specific gravity:** 1.0  
**Density:** 9.5 lb/gl  
**Solubility:** Soluble in water  
**Evaporation rate:** Lower than ether  
**Voc:** 0.05 lb/gl



- 10 STABILITY AND REACTIVITY**      Stability: Stable  
Condition of Reactivity: Heat. Incompatible materials.  
Hazardous polymerization: Will not occur.  
Hazardous decomposition products: May include, and are not limited to carbon dioxide and monoxide.  
Incompatibility: Acids, aluminum.
- 11 TOXICOLOGICAL INFORMATION**      Effects of chronic exposure and carcinogenicity: Not hazardous by WHMIS/OSHA criteria.
- 12 ECOLOGICAL INFORMATION**      Not Available
- 13 DISPOSAL INFORMATION**      This product must be disposed in compliance with local, state, and federal regulations.
- 14 TRANSPORT INFORMATION**      DOT Shipping label. NOT REGULATED.
- 15 REGULATORY INFORMATION**      **State regulation:**  
Cement Pro LLC as a blender of processed material in the State of California, we are required by Proposition 65 to warn that the following chemicals are present in this product in small amount. These chemicals are listed by the California EPA as materials known to the State of California to cause cancer, and/or birth defects, and/or other reproductive harm. The State of California (Proposition 65) requires the above warning in the absence of definitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacture, distribution and intended use. Acrylic copolymer -> California, Proposition 65.
- OSHA:** This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA).
- EPA VOC Regulations:** 0.05 lb/gal (0 g/l)
- 16 OTHER INFORMATION**      **HMIS RATING**  
**HEALTH:** 1  
**FIRE:** 0  
**REACTIVITY:** 0  
**PERSONAL PROTECTION:** E