





PATCH PRO

MATERIAL SAFETY TECHNICAL DATA SHEET



Flexible product used to patch and smooth concrete surfaces prior to the installation.

PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME:

PATCH PRO

CHEMICAL FAMILY:

Modified Portland Cement based patcher

MANUFACTURER:

CEMPRO LLC 3929 E Guasti Rd Unit C. Ontario, Ca 91761 Phone: 951 300 0300 www. cementpro.com

2 COMPOSITION AND INFORMATION ON INGREDIENTS

INGREDIENT	CAS NUMBER	PERCENT (WTT)
Portland Cement	65997-15-1	30-50%
Vinyl copolymer	Not established	0-3%
Calcium carbonate	1317-65-3	40-70%
Silica sand	14808-60-7	40-70%

3 HAZARDS IDENTIFICATION

Primary routes of entry: Inhalation, skin contact, eye contact, ingestion. Inhalation exposure: May cause nose, throat, and lung irritation, cough, labored breathing. Maycause delayed lung injury.

Skin contact: Exposure to dry Portland cement may cause drying of skin with consequent mild irritation. Prolonged contact with wet Portland cement may cause severe and irreversible damage to the skin in the form of chemical burns.

Eyes contact: Exposure to dry Portland cement can cause immediate or delayed irritation or inflammation.

Ingestion: May be harmful because the product contains Portland cement which is caustic.

Chronic (Cancer) information: Contains silica sand, known human carcinogen (category 1).



FIRST AID **MEASURES** Inhalation: Remove to fresh air. Get medical attention immediately.

Skin contact: Promptly wash contaminated skin with water and soap or mild detergent. Get medical attention immediately if the irritation, redness, rash or blistering develops and persists.

Eye contact: Flush eyes with plenty of water for 15 minutes. Get medical attention

immediately if the irritation persists.

Ingestion: DO NOT INDUCE VOMITING. If the person is conscious give some water.

Get medical attention immediately.

FIGTHING **MEASURES** Flash point: Not applicable. NOT FLAMMABLE OR COMBUSTIBLE.

Flammable limits: Not applicable

Autoignition Temperature: Not applicable

Fire extinguishing materials: Water spray, foam, carbon dioxide, dry chemical.

Special fire fighting procedures: Not applicable. Unusual fire and explosion hazards: Not applicable.

DISPOSAL **PROCEDURES**

Avoid generating dust. Collect by sweeping and scooping. Transfer collected material to a container. Wear appropriate equipment to prevent skin and eyes contact and use a dust mask. For wet material, scoop up and transfer to a container, allow material to dry

before disposal.

Note: Dispose of all wastes in accordance with federal, state and local regulations.

HANDLING AND STORAGE

Handling and storage precautions: Use only with adequate ventilation. Wear

appropriate protective equipment.

Handling precaution: Avoid creating dust. Avoid breathing dust and contact with eyes,

skin and clothes.

Storage precautions: Keep dry until use. Keep spilled products out of streams and

water systems.

EXPOSURE CONTROL AND

Ventilation: Use with adequate ventilation.

Respiratory protection: A NIOSH approved dust mask if personal exposure cannot be

controlled below applicable limits by ventilation.

PERSONAL Skin protection: Use impervious gloves if the hands will be exposed.

Eye protection: Safety glasses or goggles recommended. PROTECTION

PHYSICAL AND CHEMICAL **PROPERTIES**

Appearance: Grav powder.

Odor: Odorless

Chemical type: Mixture Physical state: Solid

Boiling point: Not applicable

Specific gravity: 2.1

Vapor density: Not applicable

Solubility: Dispersible

Evapotation rate: Not applicable

Voc: 0.0 lb/gl (0 g/l)



10 STABILITY AND REACTIVITY

Stability: STABLE

Hazardous polymerization: Will not occur.

Hazardous decomposition products: Will not spontaneously occur. Addition of water will produce calcium hydroxide, which can cause chemical burns.

Incompatibility: None known when is dry. When wet, is highly alkali, as a result, it is incompatible with acids, ammonium salts, aluminum and other alkali and alkaline earth metals.

TOXICO-LOGICAL INFORMATION Chronic / carcinogenicity: Contains silica sand, known human carcinogen (category 1). Ingredients / carcinogenicity: May contents traces of silica.

12 ECOLOGICAL INFORMATION

No data available

13 DISPOSAL INFORMATION

This product must be disposed in compliance with local, state, and federal regulations.

TRANSPORT INFORMATION

DOT Shipping label. NOT REGULATED.

15 REGULATORY INFORMATION

State regulation: Cement Pro LLC as a blender of processed material in the State of California, we are required by Proposition 65 to warn that one or more of the components contained in this product could contain chemicals known to the State of California to cause cancer, birth defects or other reproductive arm. The State of California (Proposition 65) requires the above warning in the absence ofdefinitive testing to prove that the defined risks do not exist. We believe this product complies with all other applicable state and federal laws and regulations governing manufacture, distribution and intended use.

Vinyl Copolymer - California, Proposition 65.

OSHA: This Material Safety Data Sheet is prepared to comply with the United States

EPA VOC Regulations: 0.0 lb/gl (0 g/l)

16 OTHER INFORMATION

HMIS Rating

HEALTH: 1 FIRE: 0

REACTIVITY: 0

PERSONAL PROTECTION: E