



# REMOVER PRO

## TECHNICAL DATA SHEET



Updated: February, 2024.

## PRODUCT DESCRIPTION

Remover Pro is a liquid formulation designed to tackle even the toughest dried cement-based residues on tools and surfaces. Unlike traditional acidic cleaners, which can be hazardous and corrosive, Remover Pro is non-fuming, non-corrosive, and 100% biodegradable, making it a safer choice for both users and the environment. Say goodbye to harsh fumes and potential damage to your tools and surfaces. With Remover Pro, you can enjoy a safe and pleasant working environment while effectively removing stubborn cement-based residues. Don't settle for outdated, harmful cleaners. Embrace the future of sustainable cleaning with Remover Pro.

*Available in 900 mL spray bottle*

## WHERE TO USE

- For dissolving cured cement (concrete, masonry, mortar, stucco or grout} of tools and other surfaces.
- Can be used to clean dried concrete residue on siding, vinyl, wooden decks, etc. without damaging the surface.
- See limitations before using.

## LIMITATIONS

- Only use when temperatures are between 50° F and 95° F.
- Do not use on concrete pavers.

## MIXING

- Product is ready to use.
- Do not dilute with any other material.

## APPLICATION

- 1 Do not wet the surface before application.
- 2 Thoroughly saturate the hardened cement-based product (concrete, masonry, mortar or stucco) to be removed with Remover Pro.
- 3 The surface will turn white as the product reacts, breaking down the material.
- 4 Allow Remover Pro to penetrate between 10-15 minutes. Ensure the surface remains wet with Remover Pro, and do not allow it to dry. A white residue will appear once the cleaner evaporates.
- 5 Re-apply the product to reactivate until the dry cement has softened into a pasty consistency, then rinse or wipe away. Concrete and other cement-based products will begin to soften and release from the surface in approximately 20-30 minutes.
- 6 Rinse with cold water using a high-pressure washer or a garden hose with a pressure nozzle.
- 7 Repeat cleaning directions on extra thick build-up until the build-up has softened.
- 8 Multiple applications may be required in complicated areas or areas with a thick layer of cement-based product and could be helped mechanically.
- 9 Remover Pro acts quickly but is not an instant reaction.

*Repeat steps until desired outcome has been achieved.*

TECHNICAL INFORMATION	
Shelf Life	18 months
Storage	Tightly closed container in a cool, dry and well-ventilated area
pH	3
VOCs (SCAQMD Rule #1168)	0g per L

## COVERAGE

- Coverage will vary depending on the thickness of product being removed.

## ENVIRONMENTAL INFORMATION

CementPro is committed to environmental responsibility in products produced and manufacturing practices. For information on CementPro's commitment to sustainability and transparency and how CementPro products may contribute to green building standards and certification systems, contact [sustainability@cementpro.com](mailto:sustainability@cementpro.com) or visit [www.cementpro.com/sustainability](http://www.cementpro.com/sustainability).

// KEEP OUT OF REACH OF CHILDREN //

## PRECAUTIONARY STATEMENTS

- Do not take internally.
- If swallowed, immediately drink 1 or 2 glasses of water and call a physician.
- Avoid eye and skin contact, wear approved safety equipment, goggles and gloves, if eye contact occurs, flush immediately with water for 15 minutes and consult a physician.
- If any material gets into the eyes, rinse immediately and repeatedly with water, and seek prompt medical attention.

For detailed information on how to use and handle this product safely, see the [Material Safety Data Sheet](#).

### LEGAL NOTICE

This Product Data Sheet has been prepared in good faith based on information available at the time of publication. It is intended to provide users with information and guidelines for properly using and applying the covered CementPro brand product(s) under normal environmental and working conditions. Because each project is different, CementPro cannot be responsible for the consequences of variations in such conditions or unforeseen conditions.

### WARRANTY

Every Remover Pro purchase enjoys a standard 1-year limited warranty, safeguarding its quality and performance. Head to <https://cementpro.com/warranty/> for complete details on the standard warranty specifics. At CementPro, we stand behind our products and your satisfaction.



### FOR WARRANTY QUESTIONS

Write to: 3929 E Guasti Rd, Unit C Ontario, CA 91761  
Call: (951) 300-0300 Ext. 600  
Email: [Warranty@cementpro.com](mailto:Warranty@cementpro.com)